

Submittal Data Sheet - 5MXM48AVJU9

Daikin MXM R-32 Standard Multi-Zone Outdoor Unit

Prepared for Volusion downloadable document organization. Source data is from Daikin City generated submittal information.

Field	Value
Submittal Description	R-32 Standard Multi - 5 Port Heat Pump, Ductless ODU 4 Ton
SEER2 / EER2 / HSPF2	20.00 / 10.00 / 9.50
Rated Cooling / Heating	46,000 BTU/h / 48,500 BTU/h
Operating Range	Cooling: 14°F - 115°F; Heating: 5°F - 75°F
Power Supply	208-230 V / 60 Hz / 1 phase
System MCA / MFA	38.1 A / 40.0 A
Max System Piping Length	262 ft
Refrigerant	R-32; factory charge 6.94 lb; additional charge 0.22 oz/ft
Airflow / Sound	3,137 CFM high; 55 dBA cooling / 57 dBA heating
Dimensions / Weight	34-1/4 x 43-5/16 x 18-1/8 in; 219 lb

Features / Notes

- Connect 2 to 5 indoor units with one outdoor unit
- High-efficiency inverter driven swing compressor
- Standard MXM multi-zone heat pump
- Long piping lengths, up to 260 ft

Source URL: <https://myvrdrive.com/static/e7d3ebcddaf35e386b5ead0eec719aaf/5MXM48AVJU9.pdf>

Note: Daikin products are subject to continuous improvements. Confirm current specs with Daikin before final publication.